




Document No. SNW/AIS/24/751S220NPPSMZ











General Information	
Product Code	AIS-WHT-101751S220NPPSMZ
Brand	Essco
Colour	White
Туре	Complete Set For Coupled WC (S-Trap)
Material	Ceramic-Vitreous China (VC)
Product Specification	
Product Dimension	395x680x775 mm
Bowl Opening (Inner Dimension)	265x320 mm
Product Net Weight	34 kg
Product Gross Weight	38 kg
Packaging Dimension	870x410x420 mm
Outlet	Vertical
Trap Distance	S Trap - 220 mm
Outlet Hole Dimension	External diameter of outlet hole dia. Ø 100 ± 5 mm
	Horizontal distance between the wall line and the centre line of the waste outlet hole ≤ 220 mm
Product Features	Beautifull Design ,Complete Trap Glaze, Combined Paking PP Normal Close Slim Seat Cover,Accessories Dual Flushing - 3/6 LPF, Anti germ glaze. Material - Vitreous China (VC)
ACCESSORIES INCLUDED	
Seat Cover	AIS-WHT-103N
Floor fixing screw	ZPS-SNS-FB01
Cistern Fittings	ZCF-WHT-FT003
Cistern	AIS-WHT-101201C
Wax Seal	ZPS-WHT-1401

CARE AND CLEANING GUIDELINES

- ¬ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- ¬ The product is heavy and it is recommended that two persons hold it while it is being fixed.
- ¬ Carefully inspect the new product for damage before installation.
- Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- ¬ Risk of external leakage. Do not lift or rock the bowl after placement.
- ¬ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- Do not allow cleaners to sit or soak on the product.
- Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ¬ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- n Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- \neg Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

QUALITY MANAGEMENT SYSTEM - ISO 9001





DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.