


esscobathware.com Document No. SNW/CMS/24/801/305











BACK VIEW

395	Ø35-	(502	-)
750	04	5		//
ļ <u>!</u> ::::		470		_
	TO	P VIE	W	

General Information				
Product Code C	CMS-WHT-103801 + CMS-WHT-103305			
Brand E	Essco			
Colour	White			
Type	Wall Hung Basin with pedestal			
Material C	Ceramic-Vitreous China (VC)			
Product Specification				
Product Dimension 5	540x395x185 mm With pedestal 440 mm			
Basin Inner Dimension 4	470x250x140 mm			
Product Net Weight 1	10.5 kg.			
Product Gross Weight 1	11.5 kg.			
Packaging Dimension 5	550x200x405 mm			
Outlet	Vertical			
Т	Tap hole dia. ∅ 35 ±2 mm			
I '	Internal diameter of outlet hole dia. Ø45 +2/-1 mm			
	Horizontal distance between the center line of the tap hole and the center line of the waste outlet hole ≤ 117 mm			
Product Features	Basin With Tap Hole, Packed with Overflow Hole Cap and Fixing Accessories Anti germ glaze. Material - Vitreous China (VC)			
ACCESSORIES INCLUDED				
Overflow hole cap	ZPS-WHT-9012			
Basin fixing screw Z	ZPS-MST-RB03			

ACCESSORIES RECOMMENDATION

CMS-WHT-103305 Full Pedestal Fixing Screw For Half Pedestal ZPS-MST-FB05

CARE AND CLEANING GUIDELINES

- ¬ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- ¬ The product is heavy and it is recommended that two persons hold it while it is being fixed.
- Carefully inspect the new product for damage before installation.
- \neg Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- Risk of external leakage. Do not lift or rock the bowl after placement.
- ¬ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- Do not allow cleaners to sit or soak on the product.
- Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ¬ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- ¬ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

QUALITY MANAGEMENT SYSTEM - ISO 9001





DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product