		4
esscobathware.com Document No.		
SNW/CMS/24/803/305		 * *snop*
General Information Product Code Brand Colour Type	CMS-WHT-103803 + CMS-WHT-103305 Essco White	BACK VIEW
Type Material	Wall Hung Basin with pedestal Ceramic-Vitreous China (VC)	
Material Ceramic-Vitreous China (VC) Product Specification		
Product Dimension	510x410x180 mm With pedestal 440 mm	
Basin Inner Dimension	440x265x130 mm	
	9.5 kg.	
Product Gross Weight	10.5 kg.	
Packaging Dimension Outlet	515x200x415 mm Vertical	
	Tap hole dia. Ø 35 ± 2 mm Internal diameter of outlet hole dia. Ø45 +2/-1 mm Horizontal distance between the center line of the tap hole and the center line of the waste outlet hole ≤ 120 mm Basin With Tap Hole,	
Product Features	Packed with Overflow Hole Cap and Fixing Accessories Anti germ glaze. Material - Vitreous China (VC)	
ACCESSORIES INCLUDED		
Overflow hole cap	ZPS-WHT-9012	
Basin fixing screw	ZPS-MST-RB03	
ACCESSORIES RECOMMENDATION		
Full Pedestal	CMS-WHT-103305 ZPS-MST-FB05	
Fixing Screw For Half Pedestal CARE AND CLEANING GUIDELINES		
- Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.		
- The product is heavy and it is recommended that two persons hold it while it is being fixed.		
- Carefully inspect the new product for damage before installation.		
Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.		
¬ Risk of external leakage. Do not lift or rock the bowl after placement.		
→ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.		
- Do not allow cleaners to sit or soak on the product.		
- Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.		
 Wipe surfaces clean and rinse completely with water immediately after applying cleaners. Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion. 		
- Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.		
QUALITY MANAGEMENT SYSTEM - ISO 9001		
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All		
dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product		
Prepared by	Checked by Approv	ved by