



TOP VIEW





	100	
General	Information	

Product Code	ORS-WHT-105951SPP
Brand	Essco
Colour	White
Туре	Wall Mounted WC - P TRAP

Material Ceramic-Vitreous China (VC)

345x485x345 mm

240x310 mm

23 Kg

Product	Specification
Product	Dimension

Product Net Weight

Bowl Opening (Inner Dimension)

Product Gross Weight	27 Kg
Packaging Dimension	405x385x500 mm
Outlet	Horizontal
Inlet Hole And Outlet Hole Dimension	Internal diameter of inlet hole dia. Ø 58 ± 3 mm
	External diameter of outlet hole dia. Ø 100 ± 5 mm
Product Features	Beautifull Design In Rectangular Shap For Small Size Bathroom
	PP Normal Close Seat Cover, Water Usage - 3/6 LPF With Wash Down Flushing
	Anti Bacterial Glaze on Ceramic, Smooth Glaze Surface, Material - Vitreous China (VC)
	Product With Complete Genuine Accessories
	Complete Trap Wash,Box Rim Design

ACCESSORIES INCLUDED

Seat cover	ORS-WHT-101S
Inlet Outlet Gaskit	ZPS-WHT-GK01

ACCESSORIES RECOMMENDATION

Rag bolt		ZPS-SNS-RB01 , ZPS-MST-RB02, ZPS-MST-RB07
Concealed cis	tern	JCS-WHT-2400S, 2400P, 2400, 2400WS, 2400WP, 2400FS, 2400FP, 2431P, 2431FP, 2431, 2431S, 2431FS

CARE AND CLEANING GUIDELINES

- Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- \neg The product is heavy and it is recommended that two persons hold it while it is being fixed.
- ¬ Carefully inspect the new product for damage before installation.
- ¬ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- \neg Risk of external leakage. Do not lift or rock the bowl after placement.
- Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- \neg Do not allow cleaners to sit or soak on the product.
- \neg Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ¬ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- ¬ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

QUALITY MANAGEMENT SYSTEM - ISO 9001



DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.
For Installation Refer Actual Product