



**SPECIFICATION DATA SHEET**
**PRODUCT DETAILS**

<b>Manufacturer :</b>	ESSCO	<b>Type:</b>	Wall Hung Basin with full Pedestal
<b>Range</b>	Essco	<b>Colour:</b>	White
<b>Outlet</b>	Horizontal	<b>Material:</b>	Ceramic - Vitreous China
<b>Technical Details:</b>	Diameter of the tap hole 35 $\varnothing$ +2 -1 mm,	<b>BOM doc.NO.</b>	ESW/02/2018/047
	ID of waste outlet hole 45 $\varnothing$ +2 -1 mm		ESW/02/2018/048
Horizontal distance between the centre line of the tap hole and the centre line of the waste outlet hole $\leq$ 140 mm			


**ARTICLE NAME: WALL HUNG BASIN**

**TECHNICAL DIMENSIONS**


TOP VIEW



SIDE VIEW



BACK VIEW

 ALL DIMENSIONS ARE IN MM.  
(TOLERANCE  $\pm$  5 MM)

**PRODUCT DIMENSIONS**

Length (mm)	Width (mm)	Height (mm)	Net weight (kg)
555	410	875	20

**USP**

Basin with Tap Hole, Packed with Overflow Hole Cap and Fixing Accessories(

**ACCESSORIES PROVIDED**

Overflow hole Cap	ZPS-WHT-9012
Basin fixing screw	ZPS-MST-RB03

**CARE AND CLEANING GUIDELINES**

- ★ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- ★ The product is heavy and it is recommended that two persons hold it while it is being fixed.
- ★ Carefully inspect the new product for damage before installation.
- ★ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- ★ Risk of external leakage. Do not lift or rock the bowl after placement.
- ★ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- ★ Do not allow cleaners to sit or soak on the product.
- ★ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ★ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- ★ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- ★ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

**CERTIFICATION**

Compliance : IS 2556.4:2004, IS 2556.1:1994, BS EN 14688 :2015/CE

All technical dimensions are in accordance to British standards, Bureau of Indian Standards


**PACKAGING DETAIL**

PACKAGING DETAIL				LOADING Pallet DETAIL				
Length (mm)	Width (mm)	Height (mm)	Gross Weight(kg)	Length (mm)	Width (mm)	Height (mm)	no of pieces on pallet	
Basin	560	410	200	14.5	1140	1140	2285	52
Pedestal	735	180	195	6.7	1140	1140	2285	64



Prepared By Designer Date	Controlled By Quality control	Verified By Product Manager	Approved By Sanitaryware Head
Revision/Version	1	Plotter Updated on	Month
			09-Jul Year 2018