

# MVS-WHT-951NPP

#### SPECIFICATION DATA SHEET

#### PRODUCT DETAILS

TRODUCT DETAILS						
Manufacturer :	Essco	Туре:	Wall hung WC (water closet)			
Range	Marvel	Flush valves	Regular, Dual & I Flush advantages			
Colour:	White	Material:	Ceramic - Vitreous China			
Outlet	Vertical	BOM doc.NO.	ESW/02/2018/001			
	1 1 1 1 6 1 1 1 6 50 2 4					

Technical Details: Internal diameter of inlet hole Ø 58 +2 -1 mm


External diameter of outlet hole Ø 100 +5 -2 mm


## ARTICLE NAME: WALL HUNG WC






#### TECHNICAL DIMENSIONS







TOP VIEW

SIDE VIEW

BACK VIEW

ALL DIMENSIONS ARE IN MM. (TOLERANCE ± 5 MM)

PRODUCT DIMENSIONS				USP		
Length (mm)	Width (mm)	Height (mm)	Net weight (kg)			
355	500	325	12.5	Complete Trap Glaze, packed with Inlet Outlet Gasket		
ACCESSORIES PROVIDED						
PP Normal Close Seat cover				ECS-WHT-109N		
Inlet & Outlet gasket				ZPS-WHT-GK01		
ACCESSORIES RECOMMENDED						
Rag bolt				ZPS-SNS-RB01 & ZPS-MST-RB02		
Concealed cistern model no				JCS-WHT-2400S,2400FS,2400WS		





# CARE AND CLEANING GUIDELINES

- \* Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- ★ The product is heavy and it is recommended that two persons hold it while it is being fixed.
- $\bigstar$  Carefully inspect the new product for damage before installation.
- igstar Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- ★ Risk of external leakage. Do not lift or rock the bowl after placement.
- ★ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- ★ Do not allow cleaners to sit or soak on the product.
- ★ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ★ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- ★ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- ★ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

## CERTIFICATION

Compliance: IS 2556.2:2004, IS 2556.1:1994, EN 997:2012+A1/CE
All technical dimensions are in accordance to British standards, Bureau of Indian Standards





PACKAGING DETAIL				LOADING PALLET DETAIL			
Length (mm)	Width (mm)	Height (mm)	Gross Weight(kg)	Length (mm)	Width (mm)	Height (mm)	No of pieces on pallet
410	385	535	15	1140	1140	2285	16





Prepared By	Controlled By	Verified By	Approved By	
Designer	Quality control	Product Manager	Sanitaryware Head	
Date				
Revision/Version 1		Plotter Updated on Month	17-Aug Year 2019	
		•		